

## CONVERSION TABLES

### PLAIN STRINGS

### ← | → METAL WOUND NYLON OR SILK STRINGS

GutNylgut mm -----	Nylon mm -----	PVF Carbon fibre -----	Aquila D (Gut Equiv) -----	Pyramid Gauges -----	Savarez NFA-NFC (approx) -----	Kürschner VN KN VS -----
.36	.40	.30	73	905	-	-
.38	.42	.33	76	906M	-	-
.40	.46	.35	79	906	-	-
.42	.475	.37	82	1006	70 - 72	5082
.44	.50	.38	85	9075	-	5085
.46	.525	.40	88	1007	80 - 82	5088
.48	.54	.42	91	1008	90 - 92	5091
.50	.56	.44	94	909	-	5094
.52	.575	.46	97	1009	100 - 102	5097
.54	.60	.47	100	10095	110 - 112	5100
.56	.625	.48	104	1010	120 - 122	5104
.58	.65	.50	108	1011	130 - 132	5108
.60	.675	.52	112	10105	-	5112
.62	.70	.54	116	1012	150 - 152	5116
.64	.725	.56	120	1013	170 - 172	5120
.66	.75	.57	124	1014	-	5124
.68	.775	.60	128	1015	-	5128
.70	.80	.62	132	1016	190 - 192	5132
.73	.825	.64	136	1116	-	5136
.76	.85	.66	140	1017	210 - 212	5140
.79	.875	.68	145	1018	-	5145
.82	.925	.72	150	1019	230 - 232	5150
.85	.95	.74	155	1020	250 - 252	5155
.88	.975	.76	160	1021	275 - 275	5160
.91	1.00	.79	165	1022	300 - 300	5165
.94	1.04	.83	170	1024	325 - 322	5170
.97		.85	175	1025	350 - 352	5175
1.00		.89	180	1026	-	5180
1.04		.91	185	1027	375 - 380	5185
1.08			190	1028	-	5190
1.12			195	1029	410 - 412	5195
1.16			200	1030	430 - 442	5200
1.20			210	1032	500 - 482	5210
1.24			220	1034	-	5220
1.28			230	1036	-	5230
1.32			240	1038	530 - 520	5240
1.36			245	1239	560 - 522	5250
1.40			250	1240	NFC 622	5260
1.45			260	1440		5270
1.50						5280
1.55						5290
1.60						
1.65						
1.70						
1.80						
1.85						
1.90						
1.95						
2.00						